

**MONBAT Formula A77B3P0\_1 70 Ah**

According to EN 50342


**Formula**

SEALED MAINTENANCE FREE


Your supplier  
**GACELL®**  
The right battery

GACELL A/S · Sletten 17 · 7500 Holstebro · DK  
+45 961 02 961 · www.gacell-power.dk

**Electrical specification**

|                                 |                    |
|---------------------------------|--------------------|
| <b>Voltage:</b>                 | <b>12V</b>         |
| <b>Capacity C<sup>20</sup>:</b> | <b>70 Ah</b>       |
| <b>Cold cranking current:</b>   | <b>640 A [EN]</b>  |
| <b>Cold cranking current:</b>   | <b>395 A [DIN]</b> |

**Mechanical specification**

|                                             |                        |
|---------------------------------------------|------------------------|
| <b>Dimensional group:</b>                   | <b>LB3</b>             |
| <b>ETN reference:</b>                       | <b>570 014 064 SMF</b> |
| <b>DIN reference:</b>                       | <b>57014</b>           |
| <b>Dimensions<sup>A</sup> in mm (LxWxH)</b> | <b>278x175x175</b>     |
| <b>Cell Layout:</b>                         | <b>0</b>               |
| <b>Terminal Type:</b>                       | <b>1</b>               |

**Container**

|             |                         |                      |
|-------------|-------------------------|----------------------|
| <b>Case</b> | <b>Material</b>         | <b>Polypropylene</b> |
|             | <b>Bottom hold-down</b> | <b>B4</b>            |
|             | <b>Colour</b>           | <b>Black</b>         |

|            |                     |                      |
|------------|---------------------|----------------------|
| <b>Lid</b> | <b>Material</b>     | <b>Polypropylene</b> |
|            | <b>Cover design</b> | <b>SMF</b>           |
|            | <b>Colour</b>       | <b>Black</b>         |

|                  |                 |                      |
|------------------|-----------------|----------------------|
| <b>Vent caps</b> | <b>Material</b> | <b>Polypropylene</b> |
|                  | <b>Type</b>     | <b>SMF</b>           |
|                  | <b>Colour</b>   | <b>Black</b>         |



|                |                 |                      |
|----------------|-----------------|----------------------|
| <b>Handles</b> | <b>Material</b> | <b>Polypropylene</b> |
|                | <b>Position</b> | <b>Top - on lid</b>  |
|                | <b>Colour</b>   | <b>Black</b>         |

**Battery classification as per EN 50342-6**

|                          |                         |                             |                        |
|--------------------------|-------------------------|-----------------------------|------------------------|
| <b>Water consumption</b> | <b>Charge retention</b> | <b>Vibration resistance</b> | <b>Endurance Level</b> |
| <b>W4</b>                | <b>C2</b>               | <b>V1</b>                   | <b>E1</b>              |

**Weight<sup>B</sup>**

|                                    |              |
|------------------------------------|--------------|
| <b>Battery weight in kg:</b>       | <b>11.00</b> |
| <b>Acid weight in kg:</b>          | <b>5.50</b>  |
| <b>Total battery weight in kg:</b> | <b>16.50</b> |

**Layout**

**Hold-down**

**Separator**

|             |           |
|-------------|-----------|
| <b>Type</b> | <b>PE</b> |
|-------------|-----------|

<sup>A.</sup> Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.

<sup>B.</sup> Weight may vary ±5%.