

**MONBAT Formula A99B5P0\_1 95 Ah**

According to EN 50342



**Formula**

SEALED MAINTENANCE FREE



GACELL A/S · Sletten 17 · 7500 Holstebro · DK  
+45 961 02 961 · www.gacell-power.dk

**Electrical specification**

|                            |             |
|----------------------------|-------------|
| Voltage:                   | 12V         |
| Capacity C <sup>20</sup> : | 95 Ah       |
| Cold cranking current:     | 800 A [EN]  |
| Cold cranking current:     | 490 A [DIN] |

**Mechanical specification**

|                                       |                 |
|---------------------------------------|-----------------|
| Dimensional group:                    | LB5             |
| ETN reference:                        | 595 021 080 SMF |
| DIN reference:                        | 59521           |
| Dimensions <sup>A</sup> in mm (LxWxH) | 353x175x175     |
| Cell Layout:                          | 0               |
| Terminal Type:                        | 1               |

**Container**

|      |                  |               |
|------|------------------|---------------|
| Case | Material         | Polypropylene |
|      | Bottom hold-down | B4            |
|      | Colour           | Black         |

|     |              |               |
|-----|--------------|---------------|
| Lid | Material     | Polypropylene |
|     | Cover design | SMF           |
|     | Colour       | Black         |

|           |          |               |
|-----------|----------|---------------|
| Vent caps | Material | Polypropylene |
|           | Type     | SMF           |
|           | Colour   | Black         |

|         |          |               |
|---------|----------|---------------|
| Handles | Material | Polypropylene |
|         | Position | Top - on lid  |
|         | Colour   | Black         |


**Battery classification as per EN 50342-6**

|                   |                  |                      |                 |
|-------------------|------------------|----------------------|-----------------|
| Water consumption | Charge retention | Vibration resistance | Endurance Level |
| W4                | C2               | V1                   | E1              |



**Weight<sup>B</sup>**

|                             |       |
|-----------------------------|-------|
| Battery weight in kg:       | 14.00 |
| Acid weight in kg:          | 7.20  |
| Total battery weight in kg: | 21.20 |

**Layout**



**Hold-down**



**Separator**

|      |    |
|------|----|
| Type | PE |
|------|----|

- <sup>A.</sup> Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.  
<sup>B.</sup> Weight may vary ±5%.