File No.: EBO2112135-M333 Date of Issue: January 1, 2022 Page 1 of 6

1. Identification of Substance

Product Details

Product Name:

Product Model:



NI-CD RECHARGEABLE BATTERY

Ni-CD:AA100mAh, AA150mAh, AA200mAh, AA250mAh, AA300mAh, AA350mAh, AA400mAh, AA450mAh, AA500mAh, AA600mAh, AA700mAh, AA800mAh, AA900mAh, AA1000mAh, AA1100mAh, AA1200mAh, AA1300mAh, AA1400mAh, AA1500mAh, AA1600mAh, AA1700mAh, AA1800mAh, AA1900mAh, AA2000mAh, AA2100mAh, AA2200mAh, AA2300mAh, AA2400mAh, AA2500mAh, AA2600mAh

Ni-CD: AAA100mAh, AAA150mAh, AAA200mAh, AAA250mAh, AAA300mAh, AAA350mAh, AAA400mAh, AAA450mAh, AAA500mAh, AAA600mAh, AAA700mAh, AAA800mAh, AAA900mAh, AAA1000mAh

Ni-CD: 2/3AA100mAh, 2/3AA150mAh, 2/3AA200mAh, 2/3AA250mAh, 2/3AA300mAh, 2/3AA350mAh, 2/3AA400mAh, 2/3AA450mAh, 2/3AA500mAh, 2/3AA550mAh, 2/3AA600mAh

Ni-CD: 2/3AAA100mAh, 2/3AAA150mAh, 2/3AAA200mAh, 2/3AAA250mAh, 2/3AAA300mAh, 2/3AAA350mAh, 2/3AAA400mAh, 2/3AAA450mAh, 2/3AAA500mAh, 2/3AAA500mAh

Ni-CD: 4/5AA100mAh, 4/5AA200mAh, 4/5AA300mAh, 4/5AA350mAh, 4/5AA400mAh, 4/5AA500mAh, 4/5AA600mAh, 4/5AA700mAh, 4/5AA800mAh, 4/5AA900mAh, 4/5AA1000mAh, 4/5AA1100mAh, 4/5AA1200mAh, 4/5AA1300mAh, 4/5AA1400mAh, 4/5AA1500mAh, 4/5AA1600mAh, 4/5AA1700mAh, 4/5AA1800mAh, 4/5AA1900mAh

Ni-CD: 4/5SC600mAh, 4/5SC700mAh, 4/5SC800mAh, 4/5SC900mAh, 4/5SC1000mAh, 4/5SC1100mAh, 4/5SC1200mAh, 4/5SC1300mAh, 4/5SC1400mAh, 4/5SC1500mAh, 4/5SC1600mAh, 4/5SC1700mAh, 4/5SC1800mAh, 4/5SC1900mAh, 4/5SC2000mAh

Ni-CD: SC600mAh, SC700mAh, SC800mAh, SC900mAh, SC1000mAh, SC1100mAh, SC1200mAh, SC1300mAh, SC1400mAh, SC1500mAh, SC1600mAh, SC1700mAh, SC1800mAh, SC1900mAh, SC2000mAh, SC2200mAh, SC2400mAh, SC2600mAh, SC2800mAh, SC3000mAh Ni -CD: C1500mAh, C1600mAh, C1700mAh, C1800mAh, C1900mAh, C2000mAh, C2100mAh, C2200mAh, C2300mAh, C2400mAh, C2500mAh, C2600mAh, C2700mAh, C2800mAh, C2900mAh, C3000mAh, C3500mAh, C4000mAh

Ni -CD: D3000mAh, D3500mAh, D4000mAh, D4500mAh, D5000mAh,

File No.: EBO2112135-M333 Date of Issue: January 1, 2022 Page 2 of 6

D6000mAh, D7000mAh, D8000mAh

Product use: Our batteries are mainly applied to cordless phones, walkmans, solar lights,

electrical drills, shavers, emergency lights, and back-up power, etc.

2. Hazards Identification

Hazard description:

A sealed cell/battery is not hazardous in normal use.

In case of mistreatment (abusive charge, reverse charge, external short circuit...) and in case of fault, some electrolyte can leak from the cell through the sealing system. In these cases refer to the risks of potassium hydroxide solution (corrosive, pH > 14). The electrode materials are only hazardous, if the materials are released by mechanical damaging of the cell or if exposed to fire.

3. Composition/Data on Components

COMPONENT	CAS No.	% By wt.
NiOH	12054-48-7	16.7%
Cd(OH)2	21041-95-2	26.4%
FeO	1345-25-1	25.2%
Water	7732-18-5	18.3%
KOH	1310-58-3	8.0%
NaOH	1310-73-2	2.8%
Graphite powder	7782-42-5	2.6%

4. First aid Measures

Eyes: To flush with clean water for fifteen minutes, If the allergy remains uncured,

please turn to a doctor for help.

Skin: Remove contaminated clothing. Wash with plenty of soap and water. If irritation

occurs, get medical attention.

Inhalation: Remove from exposure, rest and keep warm. In severe cases obtain medical

attention.

Ingestion: Rinse mouth with water and drink plenty of water. Consult a doctor.

File No.: EBO2112135-M333 Date of Issue: January 1, 2022 Page 3 of 6

Further treatment: All cases of eye contamination, persistent skin irritation and casualties who

have swallowed this substance or been affected by breathing its vapours

should be seen by a Doctor.

5. Fire Fighting Measures

Extinguishing Media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Extinguishing media with limited

suitability: Water is only applicable for incipient fire.

Special Fire-Fighting Procedures: Wear full protective clothing and NIOSH-approved self-contained breathing

apparatus. Avoid inhalation of material or combustion by-products.

6. Accidental Release Measures

Person related measures: Wear personal protective equipment adapted to the situation (protection gloves,

cloth).

Environment protection measures: In the event of battery rupture, prevent skin contact and collect all released

material in a plastic lined container.

Dispose off according to the local law and rules.

Avoid leached substances to get into the earth, canalization or waters.

Treatment for cleaning: If battery casing is dismantled, small amounts of electrolyte may leak. Pack the

battery including ingredients as described above. Then clean with water (diluted

acetic acid may be helpful).

7. Handling and Storage

Prohibit mechanical or electrical damage battery.

Stored in a dry, cool and ventilated environment, to avoid temperature changes or high temperature.

Keep away from heat, avoid prolonged sun exposure.

Against short circuit, overcharge, forced discharge, or in a fire.

Battery disassembly, crush, fire or high temperatures can cause fire or explosion, prohibit short-circuit or error operation.

8. Exposure Controls and Personal Protection

Respiratory protection: If the battery leaks, the need for full ventilation.

Hand Protection: Under normal use, do not.

Personal Protection: Under normal use, do not.

Other protection: Under normal use, do not.

If the battery leaks, must wear the following protection products.

File No.: EBO2112135-M333 Date of Issue: January 1, 2022 Page 4 of 6

	Respiratory protection	In all fire situations, use self-contained breathing apparatus.
" A STATE OF THE S	Hand protection	In the event of leakage wear gloves.
	Eye protection	Safety glasses are recommended during handling.
	Other	In the event of leakage, wear chemical apron.

9. Physical and Chemical Properties

General Information

Appearance characters: Mixed with odorless battery

Voltage: 1.2V

Capacity: 8000MAH

pH: 12

10. Stability and Reactivity

Stability: Stable

Hazardous Decomposition

Products: N/A.

Conditions to Avoid: Heating, mechanical abuse and electrical abuse.

Hazardous Polymerization: If leaked, forbidden to contact with strong oxidizers, mineral acids, strong

alkalis, halogenated hydrocarbons.

11. Toxicological Information

Primary irritant effect: None, unless battery ruptures. In the event of exposure to internal contents,

corrosive fumes will be very irritating to skin, eyes and mucous membranes.

Overexposure can cause symptoms of non-fibrotic lung injury and membrane

File No.: EBO2112135-M333 Date of Issue: January 1, 2022 Page 5 of 6

irritation.

Inhalation: Lung irritant.

Skin contact: Skin irritant

Eye contact: Eye irritant.

Ingestion: Tissue damage to throat and gastro-respiratory tract if swallowed.

Medical conditions generally

aggravated by exposure: In the event of exposure to internal contents, eczema, skin allergies, lung

injuries, asthma and other respiratory disorders may occur.

12. Ecological Information

Environmental Impact: Proper use and disposal of the battery will not harm the environment.

Dispose of the battery, away from water, rain and snow.

13. Disposal Considerations

Appropriate Method of Disposal of Substance or Preparation

Dispose of the batteries in accordance with approved local, state, and federal requirements. Consult state environmental agency and/or federal EPA.

14. Transport Information

Nickel Cadmium batteries are considered to be "dry cell" batteries and are unregulated for purposes of transport by the US Department of Transportation (DOT), International Civil Aviation Administration (ICAO), International Air Transport Association (IATA 63rd edition 2022) and the International Maritime Organization (IMO).

The only requirements for shipping these batteries by DOT is Special Provision 130 which states "Batteries, dry are not subject to the requirements of this subchapter only when they are offered for transportation in a manner that prevents the dangerous evolution of heat (for example, by the effective insulation of exposed terminals).

The only requirements for shipping these batteries by ICAO and IATA 62nd edition 2021 is Special Provision A123 which states "an electrical battery or battery powered device having the potential of dangerous evolutions of heat that is not prepared so as to prevent a short circuit (e.g. in the case of batteries, by the effective insulation of exposed terminals: or in the case of equipment, by disconnection of the battery and protection of exposed terminals) is forbidden from transportation."

15. Regulations

Law Information

《Dangerous Goods Regulation》

《Recommendations on the Transport of Dangerous Goods Model Regulations》

《International Maritime Dangerous Goods》

File No.: EBO2112135-M333 Date of Issue: January 1, 2022 Page 6 of 6

《Technical Instructions for the Safe Transport of Dangerous Goods》

(Classification and code of dangerous goods)

OSHA Hazard Communication Standard Status

Toxic Substances Control Act (TSCA) Status

SARA Title III

RCRA

In accordance with all Federal, State and Local laws

16. Other Information

DISCLAIMER OF LIABILITY

The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable. Accordingly, EBO Desting Center will not be responsible for damages resulting from use of or reliance upon this information.

Prepared By

Issuing Date: J

Tel: 86-755-33126608

http://www.MSDS51.com

ebo@ebotest.com