



CTEK XS 7000

7A



PORTABLE OPERATION OR PERMANENT MOUNTING

CTEK XS 7000

The XS 7000 is the perfect universal 12 V charger. XS 7000 has no mode button - just plug in the mains and connect the battery cables to start charging. It is ideal for charging larger batteries and has been developed for either portable operation or permanent mounting.

The XS 7000 offers features such as battery diagnosis that shows if a battery can receive and retain a charge, along with unique maintenance charging.

The XS 7000 is a fully automatic 7 step charger that delivers 7 A to 12 V batteries from 14-150 Ah and is suitable for maintenance charging up to 225 Ah. The charger is IP65 classified (splash and dust proof), designed to protect vehicle electronics, and is non-sparking, reverse polarity protected, and short-circuit proof. It is delivered with a 5 year warranty.

TECHNICAL DATA

CHARGING VOLTAGE	14.4V
CHARGING CURRENT	Max 7A
TYPE OF CHARGER	7 step, fully automatic charging cycle
TYPE OF BATTERY	12 V lead-acid batteries
BATTERY CAPACITY	14-150 Ah, up to 225 Ah for maintenance
INSULATION	IP65 (splash and dust proof)



Fully automatic for optimal charging



For all lead-acid batteries



FULLY CHARGED BATTERY MAINTENANCE CHARGING



Din forhandler



GACELL®

The right battery





GACELL A/S - Sletten 17 - DK 7500 Holstebro - 961 02 961



THE SMARTEST BATTERY CHARGERS IN THE WORLD



CTEK CHARGING

-  DESULPHATION
SOFT START
-  BULK
-  ABSORPTION, **READY TO USE**
ANALYSE
-  FLOAT, **FULLY CHARGED**
PULSE, **MAINTENANCE CHARGING**



- Fully automatic charging and maintenance in 7 steps maximises battery life and performance
- Numerous accessories make it simple to use the same charger for multiple batteries
- Water-resistant so that the solution can be taken to the problem even if it's raining or snowing
- Patented maintenance charge for a unique combination of maximised life and performance
- Patented desulphation that extends battery life
- No sparks, short-circuit proof and reverse-polarity protected for trouble-free usage
- Automatic detection of end-of-life batteries that eliminates unwanted surprises

READY TO USE



The table shows the estimated time for empty battery to 80 % charge.

BATTERY SIZE (Ah)	TIME TO 80 % CHARGED
14	2 h
50	6 h
100	11 h
150	17 h

GUARANTEED QUALITY WITH CTEK

CTEK customer support is available to answer any questions related to charging and CTEK chargers. Safety, simplicity and flexibility characterise all products and solutions developed and sold by CTEK. CTEK supplies chargers to more than 60 countries throughout the world. CTEK is also a reliable OEM supplier to many of the world's most prestigious car and motorcycle manufacturers.

Contact customer support: info@ctek.com

www.ctek.com

Din forhandler



GACELL A/S - Sletten 17 - DK 7500 Holstebro - 961 02 961



THE SMARTEST BATTERY CHARGERS IN THE WORLD