

# DATA SHEET

## for MONBAT P 730 011 135 SMF

According to EN 50342  
Date of updated: 13.03.2017



**12V - 230 Ah**

### Electrical specification

Voltage:	<b>12V</b>	(V)
Capacity:	<b>230</b>	(Ah)
Cold cranking current:	<b>1350</b>	(A, EN)
Cold cranking current:	<b>815</b>	(A, DIN)

### Mechanical specification

Dimensional group:	<b>8D</b>	EN50342-2:2009
ETN reference:	<b>730 011 135</b>	
DIN reference:	<b>73011</b>	
Sizes:	<b>514x276x242</b>	(L x W x H)
Cell Layout:	<b>3</b>	
Terminal Type:	<b>1</b>	

### Container

<u>Case</u>	Material	<b>POLYPROPYLENE</b>	Colour	<b>BLACK</b>
	Bottom hold down	<b>B0</b>	Handles	-
<u>Lid</u>	Material	<b>POLYPROPYLENE</b>	Colour	<b>BLACK</b>
	Cover design	<b>SMF</b>	Handles	<b>BLACK</b>
<u>Vent cap</u>	Material	<b>POLYPROPYLENE</b>	Colour	<b>BLACK</b>
	Type	<b>SMF</b>		

### Test details

Vibration resistance:	<b>V2</b>
Endurance resistance:	<b>E2</b>

Battery weight:	<b>36.80</b>	± 0.80 (kg)
Acid weight:	<b>19.30</b>	± 0.40 (kg)
Total battery weight:	<b>56.10</b>	± 1.20 (kg)

**Separator:** Type: **PE+GM**