

CHARGESTORM® CONNECTED 2 is an improved and updated version of our advanced EV charger with a range of functions and built in safety features. Compatible with NANOGRID™, a dynamic load balancing solution, for use with multiple devices.


OUR MOST ADVANCED EV CHARGER TO DATE FOR ELECTRIC AND PLUGIN HYBRID VEHICLES

CHARGESTORM® CONNECTED 2 is a state of the art EV charger specifically designed to be safe and easy to use. It's ideal for home, business, public parking and tenantowner housing associations, and it meets all the required technical safety standards. An Ethernet cable connects the EV charger to the internet. If Ethernet cannot be used, the unit can also be supplied with an optional 3G/4G modem. Internet connection is required for portal services and app management. We support integration with all major operators in electric car charging.

APP CONTROL VIA TAKING CHARGE APP

This simple and user friendly app allows you to schedule charging, view your history, adjust charging power, manage RFID, manage software updates and adjust the display brightness.

- Charging power 1.4-3.7 kW
- Adjustable charging power via app or software
- NanoGrid™ dynamic load balancing support
- Built-in fuse, AC and DC ground fault detection, built-in energy meter
- Easy installation and lock protected for maintenance
- · Wall or pole mounted
- Ambient operating temperature from -30 °C to +50 °C
- RFID reader
- OCPP 1.5/ 1.6
- IP54 and IK10
- 2-year warranty









VERSION	2
ARTICLE NUMBER	910-17049
E-NUMBER	24 802 04
CHARGING METHOD	Mode 3
CHARGING CATEGORY	
	AC charging
OUTLET LOCKING ACTUATOR	One type 2 outlet
LOCKING ACTUATOR	Yes
POSITIONING LOAD BALANCING	Wall mounting (standard), pole (option) Options for load balancing solutions between several units (NanoGrid™ Home, NanoGrid™ Local, NanoGrid™ CTEK Grid Central).
ENERGY METER	MID (standard)
NUMBER OF PHASES	1 Phase
CHARGING CURRENT	6-16 A
CHARGING POWER	1.4-3.7 kW
FREQUENCY	50 Hz
RATED VOLTAGE (INPUT)	230 V
POWER INPUT CONNECTOR	16 mm² Terminal block
AMBIENT OPERATING TEMPERATURE	-30 °C to +50 °C
RELATIVE HUMIDITY	Up to 100% at 25 °C
ALTITUDE	< 2000 m
WEIGHT	~ 7 kg
ENCLOSURE DIMENSIONS (H X W X D)	449 x 282 x 160 mm
ENCLOSURE MATERIAL	Plastic, Metal
ENCLOSURE COLOUR (METAL)	Green
ENCLOSURE COLOUR (PLASTIC)	Black
ENCLOSURE LOCK	Vov
LINGLOSOFIL LOCK	Key
GROUND FAULT DETECTION	Built-in ground fault detection, 30 mA AC, 6 mA DC
	<u> </u>
GROUND FAULT DETECTION	Built-in ground fault detection, 30 mA AC, 6 mA DC
GROUND FAULT DETECTION GROUND FAULT RESET	Built-in ground fault detection, 30 mA AC, 6 mA DC Semi-automatic
GROUND FAULT DETECTION GROUND FAULT RESET AUTHENTICATION	Built-in ground fault detection, 30 mA AC, 6 mA DC Semi-automatic RFID, App
GROUND FAULT DETECTION GROUND FAULT RESET AUTHENTICATION RFID READER	Built-in ground fault detection, 30 mA AC, 6 mA DC Semi-automatic RFID, App Yes
GROUND FAULT DETECTION GROUND FAULT RESET AUTHENTICATION RFID READER RFID TAG STANDARD	Built-in ground fault detection, 30 mA AC, 6 mA DC Semi-automatic RFID, App Yes IS015693, IS014443A (MIFARE)
GROUND FAULT DETECTION GROUND FAULT RESET AUTHENTICATION RFID READER RFID TAG STANDARD COMMUNICATION PROTOCOL	Built-in ground fault detection, 30 mA AC, 6 mA DC Semi-automatic RFID, App Yes IS015693, IS014443A (MIFARE) OCPP 1.5/ 1.6
GROUND FAULT DETECTION GROUND FAULT RESET AUTHENTICATION RFID READER RFID TAG STANDARD COMMUNICATION PROTOCOL USER INTERFACE	Built-in ground fault detection, 30 mA AC, 6 mA DC Semi-automatic RFID, App Yes ISO15693, ISO14443A (MIFARE) OCPP 1.5/ 1.6 LED symbols
GROUND FAULT DETECTION GROUND FAULT RESET AUTHENTICATION RFID READER RFID TAG STANDARD COMMUNICATION PROTOCOL USER INTERFACE CONNECTIVITY	Built-in ground fault detection, 30 mA AC, 6 mA DC Semi-automatic RFID, App Yes ISO15693, ISO14443A (MIFARE) OCPP 1.5/ 1.6 LED symbols Ethernet (standard), 3G/4G (option) Smart phone display, Taking Charge App for Android and IOS (requires that the EV charger is
GROUND FAULT DETECTION GROUND FAULT RESET AUTHENTICATION RFID READER RFID TAG STANDARD COMMUNICATION PROTOCOL USER INTERFACE CONNECTIVITY APP SUPPORT	Built-in ground fault detection, 30 mA AC, 6 mA DC Semi-automatic RFID, App Yes ISO15693, ISO14443A (MIFARE) OCPP 1.5/ 1.6 LED symbols Ethernet (standard), 3G/4G (option) Smart phone display, Taking Charge App for Android and IOS (requires that the EV charger is connected to the cloud service Charge portal).
GROUND FAULT DETECTION GROUND FAULT RESET AUTHENTICATION RFID READER RFID TAG STANDARD COMMUNICATION PROTOCOL USER INTERFACE CONNECTIVITY APP SUPPORT COMPATIBILITY MAINS	Built-in ground fault detection, 30 mA AC, 6 mA DC Semi-automatic RFID, App Yes ISO15693, ISO14443A (MIFARE) OCPP 1.5/ 1.6 LED symbols Ethernet (standard), 3G/4G (option) Smart phone display, Taking Charge App for Android and IOS (requires that the EV charger is connected to the cloud service Charge portal). IT-net, TN-net
GROUND FAULT DETECTION GROUND FAULT RESET AUTHENTICATION RFID READER RFID TAG STANDARD COMMUNICATION PROTOCOL USER INTERFACE CONNECTIVITY APP SUPPORT COMPATIBILITY MAINS COMPLIANCE	Built-in ground fault detection, 30 mA AC, 6 mA DC Semi-automatic RFID, App Yes ISO15693, ISO14443A (MIFARE) OCPP 1.5/ 1.6 LED symbols Ethernet (standard), 3G/4G (option) Smart phone display, Taking Charge App for Android and IOS (requires that the EV charger is connected to the cloud service Charge portal). IT-net, TN-net CE, IEC 61851-1, IEC 62196-2, IEC 61439-7 Download the Declaration of Conformity from
GROUND FAULT DETECTION GROUND FAULT RESET AUTHENTICATION RFID READER RFID TAG STANDARD COMMUNICATION PROTOCOL USER INTERFACE CONNECTIVITY APP SUPPORT COMPATIBILITY MAINS COMPLIANCE APPROVAL	Built-in ground fault detection, 30 mA AC, 6 mA DC Semi-automatic RFID, App Yes ISO15693, ISO14443A (MIFARE) OCPP 1.5/ 1.6 LED symbols Ethernet (standard), 3G/4G (option) Smart phone display, Taking Charge App for Android and IOS (requires that the EV charger is connected to the cloud service Charge portal). IT-net, TN-net CE, IEC 61851-1, IEC 62196-2, IEC 61439-7 Download the Declaration of Conformity from www.ctekemobility.com
GROUND FAULT DETECTION GROUND FAULT RESET AUTHENTICATION RFID READER RFID TAG STANDARD COMMUNICATION PROTOCOL USER INTERFACE CONNECTIVITY APP SUPPORT COMPATIBILITY MAINS COMPLIANCE APPROVAL INGRESS PROTECTION	Built-in ground fault detection, 30 mA AC, 6 mA DC Semi-automatic RFID, App Yes ISO15693, ISO14443A (MIFARE) OCPP 1.5/ 1.6 LED symbols Ethernet (standard), 3G/4G (option) Smart phone display, Taking Charge App for Android and IOS (requires that the EV charger is connected to the cloud service Charge portal). IT-net, TN-net CE, IEC 61851-1, IEC 62196-2, IEC 61439-7 Download the Declaration of Conformity from www.ctekemobility.com IP54

MOUNTING AND CONNECTION

CHARGESTORM® CONNECTED 2 can be easily mounted on a wall with just 4 screws. It can also be mounted on a standard 60 mm pole (option) by attaching the mounting plate to the back of the EV charger. If you need to fit dual EV chargers, we also supply a bracket that can handle two EV chargers back to back and up to four charging outlets. The pole bracket also allows you to sew both feed and Ethernet cables directly inside it for a tidy and secure installation.

GUARANTEED QUALITY WITH CTEK

Quality is at the heart of everything we do, with safety, simplicity and flexibility characterizing all of our products and solutions. If you have any questions about our products, or would like further information about EV charging, our Customer Support Team is here to help. We are the global leader in battery management solutions, and supply products to more than 70 countries throughout the world. CTEK is also a reliable OEM supplier to many of the world's most prestigious vehicle manufacturers.

For more information visit WWW.CTEKEMOBILITY.COM





