

# PB-Li 12-100 D

Rev.-Nr.: 2.0 | 2023



# POWER BOOST

high power **battery series**

**LFP** LiFePO<sub>4</sub> LITHIUM BATTERY



## ELECTRICAL SPECIFICATIONS

Nominal Voltage	12,8 V
Nominal Capacity	100 Ah
Open Circuit Volt. @ 100%	13,3 V
Energy	1280 Wh
Internal Resistance	<50 mΩ
Consumption BMS	<100 μA
Self Discharge	<3% / month
Max. Batteries in Series	4

## DISCHARGING

Max. cont. Discharge Current	120 A
Peak Discharge Current	150 A (30 s)
BMS Discharge Cut-Off	600 A (3 s)
BMS Cut-Off	10,4 V
Reconnect Voltage	11,6 V

## TEMPERATURES

Discharge Temperature	-20 to +75°C
Charge Temperature	0 to +65 °C
Storage Temperature	0 to +40 °C

## COMMUNICATION

Bluetooth 4.0 with App Android/iOS

## MECHANICAL SPECIFICATIONS

Dimensions (LxWxH)	353 x 175 x 190 mm
Weight	12,0 kg
Terminal Type	Automotive Post
Case Material	ABS
Enclosure Protection	IP 56
Cell Type / Chemistry	Prismatic / LiFePO <sub>4</sub>

## CHARGING

Recomm. Charge Current	50 A
Max. Charge Current	100 A
Recomm. Charge Voltage	14,6 V
BMS Voltage Cut-Off	15 V

## COMPLIANCE

Certificates	CE UN38.3 UL1642 & IEC62133
Shipping Classification	UN 3480, Class 9

Din forhandler  
**GACELL**  
The right battery  
GACELL A/S - Sletten 17 - DK 7500 Holstebro - 961 02 961



valid from 07/2022