

MONBAT Garden Ku44U1X0_1 28 Ah

According to EN 50342



Garden series

SEALED MAINTENANCE FREE



GACELL A/S · Sletten 17 · 7500 Holstebro · DK
+45 961 02 961 · www.gacell-power.dk

Electrical specification

Voltage:	12V
Capacity C²⁰:	28 Ah
Cold cranking current:	250 A [EN]
Cold cranking current:	150 A [DIN]

Mechanical specification

Dimensional group:	U1R-9
ETN reference:	528 015 025 SMF
DIN reference:	52815
Dimensions^A in mm (LxWxH)	196x128x184
Cell Layout:	0
Terminal Type:	4

Container

Case	Material	Polypropylene
	Bottom hold-down	B0
	Colour	Black

Lid	Material	Polypropylene
	Cover design	SMF
	Colour	Black

Vent caps	Material	Polypropylene
	Type	SMF
	Colour	Black

Handles	Material	Polypropylene
	Position	Sides - on container
	Colour	Black


Battery classification as per EN 50342-6

Water consumption	Charge retention	Vibration resistance	Endurance Level
W3	C2	V1	E1

Weight^B

Battery weight in kg:	5.10
Acid weight in kg:	2.70
Total battery weight in kg:	7.80

Layout



Hold-down



Separator

Type	PE
-------------	-----------

A. Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.
B. Weight may vary ±5%.